



**INDUSTRIAL COMPUTERS, INC.**  
 2457 S. State St., Ann Arbor, MI 48104  
 800-992-4007 Fax: 734-662-2254  
 www.eIndustrialComputers.com

**15.1" Panel Mount Display**  
 Built to NEMA 4/12 standards  
 Superior viewing angles, contrast ratio, and brightness  
 User friendly OSD controls

SPECIFICATIONS* - MODEL FP15		
LCD Display	15.1" TFT active matrix panel	
Display Size (HxV mm)	304 x 228	
Pixel Pitch (HxV mm)	0.297 x 0.297	
Max. Resolution	XGA 1024 x 768	
Contrast Ratio	350:1 (typical)	
Brightness	250 cd/m <sup>2</sup> (typical)	
Response Time	30 ms (typical)	
Display Color	16M	
Viewing Angle	L/R	+70°~-70° (typical)
	U/D	+70°~-70° (typical)
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode	VGA 720x400 (70Hz)	
	VGA640x480 (60/66/70/72/75 Hz)	
	SVGA 800x600 (60/70/72/75 Hz)	
	XGA 1024x768 (60/70/75 Hz)	
	Mac. 832 x 624 (75Hz)	
Signal Connector	D-sub 15 pin	
Controls	Power on/off with LED, Menu, Select (up/down), Adjustment (+/-)	
OSD	Brightness, Contrast, Clock, Phase, Auto-tune, Recall	
	Auto Setup, Frequency, Phase, H-position, V-position, H-position, V-position, R.G.B. Color Drive	
Plug & Play	DDC1/2B compatible	
Power	Embedded AC input, universal 100-240Volts	
Video In (Optional)	S & RCA connector (NTSC/PAL Auto-detect)	
Operating Conditions	Temperature	5°C~40°C (32°F~104°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-90% (no condensation)
Dimensions (HxDxW inches)	14.2x2.7x17.8	
Weight (lbs)	12	

\* Specifications are subject to change without notice.