



**INDUSTRIAL COMPUTERS, INC.**  
 2457 S. State St., Ann Arbor, MI 48104  
 800-992-4007 Fax: 734-662-2254  
 www.eIndustrialComputers.com

**15.1" Rack Mount Display**  
 Built for 19" Rack Systems  
 Superior viewing angles, contrast ratio, and brightness  
 User friendly OSD controls

SPECIFICATIONS* - MODEL FR15		
LCD Display		15.1" TFT active matrix panel
Display Size (HxV mm)		304 x 228
Pixel Pitch (HxV mm)		0.297 x 0.297
Max. Resolution		XGA 1024 x 768
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m <sup>2</sup> (typical)
Response Time		30 ms (typical)
Display Color		16M
Viewing Angle	L/R	+70°~-70° (typical)
	U/D	+70°~-70° (typical)
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70Hz)
		VGA640x480 (60/66/70/72/75 Hz)
		SVGA 800x600 (60/70/72/75 Hz)
		XGA 1024x768 (60/70/75 Hz)
		Mac. 832 x 624 (75Hz)
Signal Connector		D-sub 15 pin
Controls		Power on/off with LED, Menu, Select (up/down), Adjustment (+/-)
OSD		Brightness, Contrast, Clock, Phase, Auto-tune, Recall
		Auto Setup, Frequency, Phase, H-position, V-position,
		H-position, V-position, R.G.B. Color Drive
Plug & Play		DDC1/2B compatible
Power		Embedded AC input, universal 100-240Volts
Video In (Optional)		S & RCA connector (NTSC/PAL Auto-detect)
Operating Conditions	Temperature	5°C~40°C (32°F~104°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-90% (no condensation)
Dimensions (HxDxW inches)		14x2.7x19 (8U)
Weight (lbs)		12

\* Specifications are subject to change without notice.