



INDUSTRIAL COMPUTERS, INC.
 2457 S. State St., Ann Arbor, MI 48104
 800-992-4007 Fax: 734-662-2254
 www.eIndustrialComputers.com

17.1" Open Frame Display
 Kiosk / POS / Gaming
 Superior viewing angles, contrast ratio, and brightness
 User friendly OSD controls

SPECIFICATIONS* - MODEL FR17		
LCD Display	17.1" TFT active matrix panel	
Display Size (HxV mm)	337.9 x 270.3	
Pixel Pitch (HxV mm)	0.264 x 0.264	
Max. Resolution	SXGA 1280x1024	
Contrast Ratio	350:1 (typical)	
Brightness	250 cd/m ² (typical)	
Response Time	45 ms (typical)	
Display Color	16M	
Viewing Angle	L/R	+80°~-80° (typical)
	U/D	+55°~-80° (typical)
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode	VGA 720x400 (70Hz)	
	VGA640x480 (60/66/70/72/75 Hz)	
	SVGA 800x600 (60/70/72/75 Hz)	
	XGA 1024x768 (60/70/75 Hz)	
	XGA 1280x1024 (60 Hz)	
Signal Connector	D-sub 15 pin	
Controls	Power on/off with LED, Menu, Select (up/down), Adjustment (+/-)	
OSD	Brightness, Contrast, Clock, Phase, Auto-tune, Recall	
	Auto Setup, Frequency, Phase, H-position, V-position, H-position, V-position, R.G.B. Color Drive	
Plug & Play	DDC1/2B compatible	
Power	Embedded AC input, universal 100-240Volts	
Video In (Optional)	S & RCA connector (NTSC/PAL Auto-detect)	
Operating Conditions	Temperature	0°C~50°C (32°F~122°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~65°C (-4°F~149°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)		
Weight (lbs)	~19	

* Specifications are subject to change without notice.