



**INDUSTRIAL COMPUTERS, INC.**  
 2457 S. State St., Ann Arbor, MI 48104  
 800-992-4007 Fax: 734-662-2254  
 www.eIndustrialComputers.com

**17.1" Rack Mount Display**  
 Built for 19" rack system  
 Superior viewing angles, contrast ratio, and brightness  
 User friendly OSD controls

SPECIFICATIONS* - MODEL FR17		
LCD Display		17.1" TFT active matrix panel
Display Size (HxV mm)		337.9 x 270.3
Pixel Pitch (HxV mm)		0.264 x 0.264
Max. Resolution		SXGA 1280x1024
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m <sup>2</sup> (typical)
Response Time		45 ms (typical)
Display Color		16M
Viewing Angle	L/R	+80°~-80° (typical)
	U/D	+55°~-80° (typical)
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70Hz)
		VGA640x480 (60/66/70/72/75 Hz)
		SVGA 800x600 (60/70/72/75 Hz)
		XGA 1024x768 (60/70/75 Hz)
		XGA 1280x1024 (60 Hz)
Signal Connector		D-sub 15 pin
Controls		Power on/off with LED, Menu, Select (up/down), Adjustment (+/-)
OSD		Brightness, Contrast, Clock, Phase, Auto-tune, Recall
		Auto Setup, Frequency, Phase, H-position, V-position,
		H-position, V-position, R.G.B. Color Drive
Plug & Play		DDC1/2B compatible
Power		Embedded AC input, universal 100-240Volts
Video In (Optional)		S & RCA connector (NTSC/PAL Auto-detect)
Operating Conditions	Temperature	0°C~50°C (32°F~122°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~65°C (-4°F~149°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)		9U - 15.75 x 3.25 x 19
Weight (lbs)		~19

\* Specifications are subject to change without notice.